

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 211 458 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
05.06.2002 Bulletin 2002/23

(51) Int Cl.7: **F23C 6/04**, F23D 14/08,
F23D 14/70, F23M 5/02

(21) Application number: 01308390.2

(22) Date of filing: 02.10.2001

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR**
Designated Extension States:
AL LT LV MK RO SI

- **Hayes, Robert R.**
Collinsville, Oklahoma 74021 (US)
- **Waibel, Richard T.**
Broken Arrow, Oklahoma 74014 (US)
- **Bussman, Wesley R.**
Tulsa, Oklahoma 74127 (US)
- **Poe, Roger**
Beggs, Oklahoma 74421 (US)

(30) Priority: 30.11.2000 US 726937

(71) Applicant: **JOHN ZINK COMPANY, L.L.C.**
Tulsa, OK 74116 (US)


(74) Representative: **Nicholls, Michael John**
J.A. KEMP & CO.
14, South Square
Gray's Inn
London WC1R 5JJ (GB)

(72) Inventors:
• **Venizelos, Demetris**
Claremore, Oklahoma 74017 (US)

(54) Low NO_x premix burner apparatus and methods

(57) Low NO_x axial premix burner apparatus and methods for burning fuel gas are provided by the present invention. The methods of the invention are basically comprised of the steps of mixing a first portion of the fuel gas and all of the air to form a lean primary fuel gas-air mixture, discharging the lean primary fuel gas-air mix-

ture into the furnace space whereby the mixture is burned in a primary combustion zone therein, discharging a second portion of the fuel gas into the primary combustion zone to stabilize the flame produced therein and discharging the remaining portion of the fuel gas into a secondary combustion zone in the furnace space.



EP 1 211 458 A2

Description

[0001] The present invention relates to low NO_x producing burner apparatus and methods, and more particularly, to low NO_x axial premix burner apparatus and methods.

[0002] Because of stringent environmental emission standards adopted by government authorities and agencies, burner apparatus and methods have heretofore been developed which suppress the formation of nitrogen oxides (NO_x) in flue gases produced by the combustion of fuel-air mixtures. For example, burner apparatus and methods wherein liquid or gaseous fuel is burned in less than a stoichiometric concentration of air to lower the flame temperature and thereby reduce thermal NO_x have been developed. That is, staged air burner apparatus and methods have been developed wherein the fuel is burned in a deficiency of air in a first combustion zone whereby a reducing environment which suppresses NO_x formation is produced, and the remaining portion of the air is introduced into a second zone downstream from the first zone wherein the unburned remaining fuel is combusted.

[0003] Staged fuel burner apparatus have also been developed wherein all of the air and some of the fuel is burned in a first zone with the remaining fuel being burned in a second downstream zone. In such staged fuel burner apparatus and methods, an excess of air in the first zone functions as a diluent which lowers the temperature of the burning gases and thereby reduces the formation of NO_x .

[0004] While staged fuel burners which produce flue gases containing low levels of NO_x have been utilized heretofore, there are continuing needs for improved axial premix burner apparatus having high firing capacities and producing flue gases having ultra low NO_x emission levels and methods of using the apparatus.

[0005] By the present invention low NO_x axial premix burner apparatus and methods are provided which meet the needs described above and overcome the deficiencies of the prior art. That is, in accordance with the present invention, a low NO_x forming premix burner apparatus for burning gaseous fuels adapted to be connected to a furnace space is provided. The burner apparatus includes a housing having a discharge end attached to the furnace space and a closed opposite end. Means for introducing air into the housing are attached thereto and a burner tile having an opening therethrough and optionally including a flame stabilizing block as a part thereof is disposed within the furnace space adjacent to the burner housing. At least one elongated primary fuel gas and air venturi mixer is disposed within the housing having an open inlet end positioned adjacent to the closed end of the housing and a primary fuel gas-air mixture discharge nozzle attached to the other end thereof. The discharge nozzle extends into the burner tile through the opening therein and is positioned so that the flame produced by the burning of the primary

fuel gas-air mixture is projected in a direction which is axial to the burner housing and impinges on the flame stabilizing block when it is utilized. A first primary fuel gas nozzle connected to a source of pressurized fuel gas is positioned to discharge a primary gas fuel jet into the open inlet end of the elongated venturi mixer whereby air from within the housing is drawn into the mixer, the air is mixed with the primary fuel gas therein and the resulting primary fuel gas-air mixture is discharged by the discharge nozzle and burned in the burner tile and in the furnace space. A second primary fuel gas nozzle connected to a source of pressurized fuel gas is positioned within the burner tile to discharge additional primary fuel gas into the flame therein whereby the flame is further stabilized. At least one secondary fuel gas nozzle connected to a source of pressurized fuel and positioned to discharge secondary fuel gas within the furnace space is provided whereby the secondary fuel gas mixes with air and flue gases in the furnace space and is burned therein.

[0006] The methods of the present invention basically comprise the following steps. (a) mixing a first portion of the fuel gas and all of the air to form a lean primary fuel gas-air mixture; (b) discharging the lean primary fuel gas-air mixture into a furnace space whereby the mixture is burned in a primary combustion zone therein and flue gases having very low NO_x content are formed therefrom; (c) discharging a second portion of the fuel gas into the primary combustion zone whereby the second portion of the fuel gas is mixed with air and is burned to further stabilize the flame produced therein; and (d) discharging the remaining portion of the fuel gas into a secondary combustion zone in the furnace space wherein the remaining portion of the fuel gas mixes with air in the furnace space and with flue gases therein to form a second fuel gas-air mixture diluted with flue gases whereby the mixture is burned in the secondary combustion zone and additional flue gases having very low NO_x content are formed therefrom. The flame produced in the primary combustion zone by the burning of the lean primary fuel gas-air mixture discharged in accordance with step (a) can optionally contact a flame stabilizing block in the furnace space.

[0007] It is, therefore, a general object of the present invention to provide an improved low NO_x axial premix burner apparatus and methods of burning an at least substantially stoichiometric mixture of fuel gas and air whereby flue gases having very low NO_x content are formed therefrom.

[0008] Other and further objects, features and advantages of the present invention will be readily apparent to those skilled in the art upon a reading of the description of preferred embodiments which follows when taken in conjunction with the accompanying drawings.

[0009] The invention will now be described by way of non-limitative example with reference to the accompanying drawings, in which:

FIG. 1 is a side elevational view of the burner apparatus of the present invention attached to a furnace space.

FIG. 2 is an end view of the burner apparatus taken along line 2-2 of FIG. 1.

FIG. 3 is an opposite end view of the burner apparatus taken along line 3-3 of FIG. 1.

FIG. 4 is a cross-sectional view of the burner apparatus taken along line 4-4 of FIG. 3.

[0010] The present invention provides a low NO_x axial premix burner which provides a high heat release and a high burner efficiency while maintaining very low NO_x formation. The burner apparatus can achieve very high firing capacity, a variety of flame shapes, excellent stability and very low NO_x emissions which meet desired performance specifications. The burner apparatus may be utilized to fire horizontally along a furnace floor, vertically up a furnace wall or at an angle along a furnace wall. Other advantages of the burner apparatus and methods of this invention will be apparent to those skilled in the art from the following description.

[0011] Referring now to the drawings, the low NO_x premix axial burner apparatus of the present invention is illustrated and generally designated by the numeral 10. The burner 10 includes a housing 12 having an open discharge end 14 and a closed opposite end 16. As illustrated in FIG. 1, the open end 14 of the housing 12 is adapted to be connected to an opening 18 in a wall 20 of a furnace. As will be understood by those skilled in the art, the furnace wall 18 generally includes an internal layer of insulation material 22 and the wall 20 and insulation material 22 define a furnace space 24 within which fuel and air are burned to form hot flue gases.

[0012] As shown in FIG. 2, an air register 26 is sealingly connected over an opening (not shown) in a side of the housing 12 for introducing a controlled quantity of air into the housing 12. The air register 26 includes louvers 28 or the like which can be adjusted by means of a handle 29 to control the quantity of air flowing there-through and into the housing 12.

[0013] A burner tile generally designated by the numeral 28 is attached to the open inlet end 14 of the housing 12 and extends into the furnace space 24 as shown in FIGS. 1 and 4. In an alternate arrangement, the burner tile 28 can be disposed in the furnace space 24 sealingly attached over the opening 18 in the wall 20 of the furnace space 24. The burner tile 28 is formed of a heat and flame resistant ceramic material and can be molded as a single part or it can be formed of a plurality of parts as shown in FIGS. 1 and 3. The burner tile 28 includes two openings 30 (FIG. 3) for receiving discharge nozzles 32 connected to a pair of fuel gas and air venturi mixers which will be described further hereinbelow. The openings 30 and the discharge nozzles 32 are surrounded by the side and bottom walls 34, 36, 38 and 40 of the burner tile 28. The center portion of the burner tile 28 surrounding the discharge nozzles 32 includes an open-

ing 42 therein. Also, a flame stabilizing block 44 can optionally be attached to or otherwise positioned adjacent to the bottom wall 38 of the burner tile 28.

[0014] As shown in FIGS. 1, 3 and 4, a pair of fuel gas and air venturi mixers 46 are axially disposed within the housing 12. The elongated venturi mixers 46 each include an open end 48 positioned adjacent to the closed end 16 of the housing 12 with the other end being connected to a previously mentioned discharge nozzle 32. The discharge nozzles 32 are positioned at slight angles such that the fuel gas and air mixtures discharged through the nozzles 32 and the flame produced from their combustion is projected towards the flame stabilizing block 44 when it is utilized. Each of the venturi mixers 46 includes an adjustable air door assembly at the open inlet end thereof generally designated by the numeral 50 (FIG. 1). Control handles 52 which are a part of the assemblies 50 are utilized to control and balance the air entering the venturi mixers 46.

[0015] As best shown in FIGS. 1 and 4, a closed compartment generally designated by the numeral 54 is disposed within the housing 20 and sealingly attached over the opening 18 in the furnace space 24. The closed compartment 54 includes an opening 56 therein (FIG. 4) and a door 58 is hinged to the compartment 54 over the opening 56. The door 58 is connected to a rod 60 which is in turn connected to a control handle mounted on the outside of the closed end of the housing 12 for opening and closing the door 58. When the door 58 is opened, air from within the housing 12 flows through the opening 56 into the closed compartment 54 and then flows into the furnace space 24 by way of the opening 42 in the burner tile 28. While the door 58 can be used to allow a controlled rate of secondary air into the furnace space 24, it is normally only used when the fuel gas-air mixtures discharged from the venturi mixers 46 are initially ignited as will be described hereinbelow.

[0016] A pair of primary fuel gas nozzles 64 are attached to the closed end 16 of the housing 12 and are positioned to discharge primary fuel gas jets into the open ends 48 of the venturi mixers 46 (only one of the nozzles 64 and one venturi mixer 46 are shown in FIG. 1). Each of the primary fuel gas nozzles 64 is connected by a conduit 66 to a fuel gas header 68 as shown in FIGS. 1 and 2. As will be understood by those skilled in the art, the primary fuel gas jets discharged into the open ends 48 of the venturi mixers 46 cause air from within the housing 12 to be drawn into the venturi mixers 46 whereby the air mixes with the discharged primary fuel gas and the resulting mixtures exit the venturi mixers 46 by way of the discharge nozzles 32 attached thereto. The discharge nozzles 32 include a plurality of openings therein designed to provide the total exit area necessary for the fuel gas-air mixtures from the venturi mixers to flow through the discharge nozzles. Also, as is well understood by those skilled in the art, the discharge nozzles 32 are of a design to insure that the burner 10 can be operated without the occurrence of flash backs.

[0017] A pair of secondary fuel gas nozzles (staged fuel gas nozzles) 70 are positioned at the end of the burner tile 28 within the furnace space 24. The secondary fuel gas tips 70 are positioned above and on opposite sides of the two fuel gas-air mixture discharge nozzles 32, and the nozzles 70 are oriented so that the secondary fuel gas is discharged into a secondary combustion zone downstream of the primary combustion zone within the furnace space 24.

[0018] The flame produced by the burning of the primary fuel gas-air mixtures discharged from the nozzles 32 impinges on the flame stabilizing block 44 when it is utilized causing the block to be heated, stabilizing the flame and establishing a mixing zone within the primary combustion zone in the furnace space 24. Because the primary fuel gas-air mixtures discharged into the primary combustion zone contain excess air, the flue gases generated in the primary combustion zone have a very low NO_x content. The secondary fuel gas discharged by the secondary fuel gas nozzles 70 into the secondary combustion zone mixes with air remaining in the furnace space and with flue gases contained therein to form a second fuel gas-air mixture diluted with flue gases which is burned in the secondary combustion zone forming additional flue gases having very low NO_x content. The secondary fuel gas nozzles 70 are connected by conduits 72 within the housing 12 and by conduits 74 outside the closed end 16 of the housing 12 to the fuel gas inlet header 68.

[0019] In order to further stabilize the flame produced in the primary combustion zone in addition to the flame stabilization brought about by the stabilizing block 44 when it is used, a primary fuel gas nozzle 76 is positioned adjacent to the primary fuel gas-air discharge nozzles 32. That is, the primary fuel gas nozzle 76 is positioned below and between the discharge nozzles 32 as best shown in FIG. 3. The primary fuel gas nozzle 76 is connected by a conduit 78 within the housing 12 and a conduit 80 outside the housing 12 to the fuel gas inlet header 68. The primary fuel gas discharged into the primary combustion zone by the fuel gas nozzle 76 mixes with air in the primary combustion zone and forms a fuel gas-air mixture therein which is substantially stoichiometric. The burning of that mixture in the primary combustion zone functions to stabilize the overall flame produced.

[0020] A conduit 82 for facilitating the ignition of the primary fuel gas-air mixtures discharged by the venturi mixer discharge nozzles 32 is sealingly connected through the closed end 16 of the housing 12 and through and into the closed compartment 54. A cover door is attached to the housing 12 over the outside end of the conduit 82. As will be understood by those skilled in the art, a torch is inserted through the conduit 82 into the closed compartment 54 and through the opening 42 for igniting the primary fuel gas-air mixture exiting the nozzles 32. Prior to inserting the torch, the air door 58 in the closed compartment 54 is opened to insure that fuel gas

does not enter the closed compartment 54 prior to ignition.

[0021] As will be understood by those skilled in the art, depending on the design conditions to be met by the burner apparatus 10, the burner apparatus can include one or more primary fuel gas-air venturi mixers, one or more first primary fuel gas nozzles for injecting primary fuel gas into the venturi mixer or mixers, one or more second primary fuel gas nozzles for stabilizing the flame in the primary combustion zone and one or more secondary fuel gas nozzles for introducing fuel gas into the secondary combustion zone. Further, a single primary fuel gas-air venturi mixer having a plurality of primary fuel nozzles therein for causing air to be drawn into the venturi mixer can be used.

[0022] The methods carried out by the burner apparatus of this invention, i.e., the methods of discharging an at least substantially stoichiometric mixture of fuel gas and air into a furnace space wherein the mixture is burned and flue gases having very low NO_x content are formed therefrom, are basically comprised of the following steps: (a) a first portion of the fuel gas (referred to herein as primary fuel gas) and all of the air are mixed in the venturi mixers 46 to form lean primary fuel gas-air mixtures; (b) the lean primary fuel gas-air mixtures are discharged into the furnace space 24 whereby the mixtures are burned in a primary combustion zone therein, the flame produced optionally contacts a flame stabilizing block 44 in the furnace space 24 and is stabilized thereby and flue gases having very low NO_x content are formed therefrom; (c) a second portion of the fuel gas (also referred to as primary fuel gas) is discharged into the primary combustion zone whereby the second portion of the primary fuel gas is mixed with air and is burned to stabilize the flame produced in the primary combustion zone; and (d) the remaining portion of the fuel gas (referred to as secondary fuel gas) is discharged into a secondary combustion zone in the furnace space 24 wherein the remaining portion of the fuel gas mixes with air remaining in the furnace space 24 and with flue gases contained therein to form a second fuel gas-air mixture diluted with flue gases whereby the mixture is burned in the secondary combustion zone and additional flue gases having very low NO_x content are formed therefrom.

[0023] As mentioned above, depending upon the particular application involved, the above described method can be carried out in a burner apparatus of this invention having one or more primary fuel gas-air venturi mixers, one or more first primary fuel gas nozzles for injecting primary fuel gas into the venturi mixer or mixers, one or more second primary fuel gas nozzles for stabilizing the flame in the primary combustion zone and one or more secondary fuel gas nozzles for introducing fuel gas into the secondary combustion zone.

[0024] The lean mixture of the first portion of the primary fuel gas and air which is discharged into the primary combustion zone is generally a mixture having a

stoichiometric ratio of fuel gas to air of about 1.5:4. The first portion of the primary fuel gas in the lean primary fuel gas-air mixture is also generally an amount in the range of from about 30% to about 70% by volume of the total fuel gas discharged into the furnace space. The second portion of the primary fuel gas discharged into the primary combustion zone to stabilize the flame is generally an amount in the range of from about 2% to about 25% by volume of the total fuel gas discharged into the furnace space. The remaining portion of the fuel gas, i.e., the secondary fuel gas, is generally discharged into the secondary combustion zone in an amount in the range of from about 25% to about 68% by volume of the total fuel gas discharged into the furnace space.

[0025] In order to further illustrate the burner apparatus and methods of the present invention, the following example is given.

Example

[0026] A burner apparatus 10 designed for a heat release of 4.8 BTU per hour by burning fuel gas having a caloric value of 1160 BTU per SCF is fired into the furnace space 24. Pressurized fuel gas is supplied to the burner 10 at a pressure of about 45 psig and at a rate of 4100 SCF per hour. A portion of the fuel gas flows into and through the primary fuel gas and air venturi mixers 46 wherein the fuel gas is mixed with air. The lean primary fuel gas-air mixtures formed in the venturi mixers 46 are discharged into a primary combustion zone in the furnace space wherein they are burned and the flame produced contacts the flame stabilizing block 44 and is stabilized thereby. A second portion of the fuel gas is discharged into the furnace space 24 by way of the primary fuel gas nozzle 76 wherein it is mixed with air and is burned to further stabilize the flame produced in the primary combustion zone. The remaining portion of the fuel gas is discharged into the furnace space by way of the secondary fuel gas nozzles 70. In this example, the rate of air introduced in the housing 12 is controlled by means of the damper 28 such that the total rate of air introduced into the furnace space 24 is an amount which results in 15% excess air therein. All of the air is introduced into the furnace space 24 by way of the venturi mixers 46.

[0027] The secondary fuel gas discharged from the secondary fuel nozzles 70 mixes with the air remaining in the furnace space 24 and relatively cool flue gases therein to form a flue gases diluted fuel-air mixture which is burned in a secondary combustion zone adjacent to the primary combustion zone in the furnace space 24.

[0028] As a result of the burning of the lean primary fuel gas-air mixture in the primary combustion zone and the flue gases diluted secondary fuel gas-air mixture in the secondary combustion zone, the flue gases exiting the furnace space 24 have a very low NO_x content. That is, the flue gases withdrawn from the furnace space 24 have a NO_x content of less than about 12 ppm.

[0029] Thus, the present invention is well adapted to carry out the objects and the ends and advantages mentioned as well as those which are inherent therein. While presently preferred embodiments of the invention have been described for purposes of this disclosure, numerous changes in the construction and in the arrangement of parts and steps will suggest themselves to those skilled in the art which are encompassed within the invention as defined by the appended claims.

Claims

1. A low NO_x axial premix burner apparatus for burning fuel gas adapted to be attached to an opening in a furnace space comprising:

a housing having a discharge end attached to said opening in said furnace space and a closed opposite end;

means for introducing air into said housing attached thereto;

a burner tile having an opening therethrough attached to said discharge end of said housing or otherwise disposed within said furnace space adjacent to said opening therein;

at least one elongated primary fuel gas and air venturi mixer disposed within said housing having an open inlet end positioned adjacent to said closed end of said housing and a primary fuel gas-air mixture discharge nozzle attached to the other end thereof;

a first primary fuel gas nozzle connected to a source of pressurized fuel gas positioned to discharge a primary fuel gas jet into said open inlet end of said elongated venturi mixer whereby air from within said housing is drawn into said mixer, mixed with said primary fuel-gas therein and the resulting primary fuel gas-air mixture is discharged by said discharge nozzle and burned in said burner tile and in said furnace space;

a second primary fuel gas nozzle connected to a source of pressurized fuel gas and positioned within said burner tile for discharging additional primary fuel gas into said flame therein to stabilize said flame; and

at least one secondary fuel gas nozzle connected to a source of pressurized fuel gas and positioned to discharge secondary fuel gas within said furnace space whereby said secondary fuel gas mixes with air and flue gases in said furnace space and is burned therein.

2. The burner apparatus of claim 1 which further comprises a flame stabilizing block attached to said burner tile or otherwise positioned in said furnace space so that the flame produced by the burning of said primary fuel gas-air mixture discharged by said



discharge nozzle impinges on said flame stabilizing block and is stabilized thereby.



3. The burner apparatus of claim 1 or 2, which further comprises an air passage in said burner tile and a closed compartment disposed within said housing and sealingly attached over said opening in said furnace space, said compartment having an air door therein which can be selectively opened to allow air to flow into said compartment and through said air passage in said burner tile into said furnace space. 5
4. The burner apparatus of claim 1, 2 or 3 which further comprises one or more additional elongated primary fuel gas and air venturi mixers having discharge nozzles attached thereto and extending into said burner tile through openings therein and having first primary fuel gas nozzles positioned to discharge primary fuel gas jets into said open inlet ends thereof. 10 15 20
5. The burner apparatus of any one of claims 1 to 4 which further comprises one or more additional secondary primary fuel gas nozzles positioned within said burner tile to further stabilize said flame. 25
6. The burner apparatus of any one of claims 1 to 5 which further comprises one or more additional secondary fuel gas nozzles. 30
7. The burner apparatus of claim 3 which further comprises a conduit for facilitating the ignition of said primary fuel gas-air mixture discharged by said venturi mixer discharge nozzle sealingly connected through said closed end of said housing at one end and sealingly connected through and into said closed compartment disposed within said housing at the other end. 35
8. A low NO_x premix axial burner apparatus for burning fuel gas adapted to be attached to an opening in a furnace space comprising: 40
 - a housing having a discharge end attached to said opening in said furnace space and a closed opposite end; 45
 - means for introducing air into said housing attached thereto;
 - a burner tile having a pair of openings there-through attached to said discharge end of said housing or otherwise disposed within said furnace space adjacent to said opening therein, said burner tile including a flame stabilizing block as a part thereof; 50
 - a pair of elongated primary fuel gas and air venturi mixers disposed within said housing, each having an open inlet end positioned adjacent to said closed end of said housing and a primary 55

fuel gas-air mixture discharge nozzle attached to the other end thereof, said discharge nozzles extending into said burner tile through said openings therein and being positioned therein so that the flame produced by the burning of said primary fuel gas-air mixtures discharged by said discharge nozzles impinges on said flame stabilizing block and is stabilized thereby; a pair of first primary fuel gas nozzles connected to a source of pressurized fuel gas, each positioned to discharge a primary fuel gas jet into an open inlet end of one of said elongated venturi mixers whereby air from within said housing is drawn into said mixers, mixed with said primary fuel-gas therein and the resulting primary fuel gas-air mixtures are discharged by said discharge nozzles and burned in said burner tile and in said furnace space; a second primary fuel gas nozzle connected to a source of pressurized fuel gas and positioned within said burner tile to discharge additional primary fuel gas into said flame therein to further stabilize said flame; and a pair of secondary fuel gas nozzles connected to a source of pressurized fuel and positioned to discharge secondary fuel gas within said furnace space whereby said secondary fuel gas mixes with air and flue gases in said furnace space and is burned therein.

9. The burner apparatus of claim 8 which further comprises an air passage in said burner tile and a closed compartment disposed within said housing and sealingly attached over said opening in said furnace space, said compartment having an air door therein which can be selectively opened to allow air to flow into said compartment and through said air passage in said burner tile into said furnace space.
10. The burner apparatus of claim 9 which further comprises a conduit for facilitating the ignition of said primary fuel gas-air mixtures discharged by said venturi mixer discharge nozzles sealingly connected through said closed end of said housing at one end and sealingly connected through and into said closed compartment disposed within said housing at the other end.
11. The burner apparatus of claim 10 wherein said air passage in said burner tile is positioned between said venturi mixer discharge nozzle openings in said burner tile.
12. A method of discharging an at least substantially stoichiometric mixture of fuel gas and air into a furnace space wherein said mixture is burned and flue gases having low NO_x content are formed therefrom comprising the steps of:

- (a) mixing a first portion of said fuel gas and all of said air to form a lean primary fuel gas-air mixture;
- (b) discharging said lean primary fuel gas-air mixture into said furnace space whereby said mixture is burned in a primary combustion zone therein and flue gases having low NO_x content are formed therefrom;
- (c) discharging a second portion of said fuel gas into said primary combustion zone whereby said second portion of said fuel gas is mixed with air and is burned to stabilize said flame produced therein; and
- (d) discharging the remaining portion of said fuel gas into a secondary combustion zone in said furnace space wherein said remaining portion of said fuel gas mixes with air remaining in said furnace space and with flue gases contained therein to form a second fuel gas-air mixture diluted with flue gases whereby said mixture is burned in said secondary combustion zone and additional flue gases having low NO_x content are formed therefrom.
13. The method of claim 12 which further comprises the step of providing a flame stabilizing block in said furnace space positioned so that the flame produced by the burning of said lean primary fuel gas-air mixture therein impinges on said flame stabilizing block and is stabilized thereby.
14. The method of claim 12 or 13 wherein said lean primary fuel gas-air mixture is formed in a primary fuel gas and air venturi mixer and discharged into said primary combustion zone through a discharge nozzle attached thereto.
15. The method of claim 12, 13 or 14 wherein said lean primary fuel gas-air mixture is formed in two or more primary fuel gas and air venturi mixers and discharged into said primary combustion zone through discharge nozzles attached thereto.
16. The method of any one of claims 12 to 15 wherein said remaining portion of said fuel gas is discharged into said secondary combustion zone by at least one secondary fuel gas nozzle.
17. The method of any one of claims 12 to 16 wherein said lean primary fuel gas-air mixture discharged into said furnace space has a stoichiometric ratio of fuel gas to air of about 1.5:4.
18. The method of any one of claims 12 to 17 wherein said first portion of said fuel gas in said lean primary fuel gas-air mixture discharged into said furnace space is an amount in the range of from about 30% to about 70% by volume of the total fuel gas discharged into said furnace space.
19. The method of any one of claims 12 to 18 wherein said second portion of said fuel gas discharged into said furnace space is an amount in the range of from about 2% to about 25% by volume of the total fuel gas discharged into said furnace space.
20. The method of any one of claims 12 to 19 wherein said remaining portion of said fuel gas discharged into said furnace space is an amount in the range of from about 25% to about 68% by volume of the total fuel gas discharged into said furnace space.





THIS PAGE BLANK (USPTO)

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 211 458 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
02.10.2002 Bulletin 2002/40

(51) Int Cl.7: **F23C 6/04, F23D 14/08,
F23D 14/70, F23M 5/02**

(43) Date of publication A2:
05.06.2002 Bulletin 2002/23

(21) Application number: **01308390.2**

(22) Date of filing: **02.10.2001**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR**
Designated Extension States:
AL LT LV MK RO SI

- **Hayes, Robert R.**
Collinsville, Oklahoma 74021 (US)
- **Waibel, Richard T.**
Broken Arrow, Oklahoma 74014 (US)
- **Bussman, Wesley R.**
Tulsa, Oklahoma 74127 (US)
- **Poe, Roger**
Beggs, Oklahoma 74421 (US)

(30) Priority: **30.11.2000 US 726937**

(71) Applicant: **JOHN ZINK COMPANY, L.L.C.**
Tulsa, OK 74116 (US)



(74) Representative: **Nicholls, Michael John**
J.A. KEMP & CO.
14, South Square
Gray's Inn
London WC1R 5JJ (GB)

(72) Inventors:
• **Venizelos, Demetris**
Claremore, Oklahoma 74017 (US)

(54) Low NO_x premix burner apparatus and methods

(57) Low NO_x axial premix burner apparatus and methods for burning fuel gas are provided by the present invention. The methods of the invention are basically comprised of the steps of mixing a first portion of the fuel gas and all of the air to form a lean primary fuel gas-air mixture, discharging the lean primary fuel gas-air mix-

ture into the furnace space whereby the mixture is burned in a primary combustion zone therein, discharging a second portion of the fuel gas into the primary combustion zone to stabilize the flame produced therein and discharging the remaining portion of the fuel gas into a secondary combustion zone in the furnace space.





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 01 30 8390

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
A	WO 99 66261 A (JOHN ZINK COMPANY L L C) 23 December 1999 (1999-12-23) * page 5, line 14 - page 11, line 21; figures 1,2 *	1,8,12	F23C6/04 F23D14/08 F23D14/70 F23M5/02
A	EP 0 751 343 A (SELAS CORP OF AMERICA) 2 January 1997 (1997-01-02) * column 3, line 49 - column 5, line 47; figures 3,4 *	1,8,12	
A	EP 0 562 710 A (ZINK CO JOHN) 29 September 1993 (1993-09-29) * column 2, line 44 - column 5, line 54; figures 1-4 *	1,8,12	
A	US 5 634 785 A (BURY FREDERIC ET AL) 3 June 1997 (1997-06-03) * the whole document *		
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			F23C F23M F23D
The present search report has been drawn up for all claims			
Place of search MUNICH		Date of completion of the search 8 July 2002	Examiner Theis, G
CATEGORY OF CITED DOCUMENTS		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application I : document cited for other reasons & : member of the same patent family, corresponding document X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document	

EPO FORM 503 03 82 (P01C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 30 8390

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

08-07-2002

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
WO 9966261	A	23-12-1999	AU	4694099 A	05-01-2000
			EP	1088187 A1	04-04-2001
			WO	9966261 A1	23-12-1999
			US	6347935 B1	19-02-2002
			US	2001049076 A1	06-12-2001
EP 0751343	A	02-01-1997	US	5709541 A	20-01-1998
			CA	2175011 A1	27-12-1996
			DE	69616881 D1	20-12-2001
			EP	1108952 A2	20-06-2001
			EP	0751343 A1	02-01-1997
			ES	2166412 T3	16-04-2002
			NO	961633 A	27-12-1996
EP 0562710	A	29-09-1993	US	5195884 A	23-03-1993
			CA	2076705 A1	28-09-1993
			EP	0562710 A2	29-09-1993
			JP	2633452 B2	23-07-1997
			JP	5018011 A	25-01-1994
US 5634785	A	03-06-1997	FR	2718222 A1	06-10-1995
			CA	2145347 A1	30-09-1995
			DE	69509816 D1	01-07-1999
			DE	69509816 T2	27-01-2000
			EP	0675321 A1	04-10-1995
			ES	2132551 T3	16-08-1999

EPO - FORM P0159

For more details about this annex see Official Journal of the European Patent Office, No. 12/82

THIS PAGE BLANK (USPTO)






US 20020064740A1

(19) **United States**(12) **Patent Application Publication**
Venizelos et al.(10) **Pub. No.: US 2002/0064740 A1**(43) **Pub. Date: May 30, 2002**(54) **LOW NO_x PREMIX BURNER APPARATUS
AND METHODS****Publication Classification**(51) **Int. Cl.⁷** **F23M 3/02; F23M 3/00;**
..... **F23C 5/02**(52) **U.S. Cl.** **431/8; 431/9; 431/347; 431/285**(76) **Inventors:** **Demetris Venizelos**, Claremore, OK
(US); **R. Robert Hayes**, Collinsville,
OK (US); **Richard T. Waibel**, Broken
Arrow, OK (US); **Wesley R. Bussman**,
Tulsa, OK (US)(57) **ABSTRACT**

Correspondence Address:
C. Clark Dougherty, Jr.
McAFEE & TAFT
Two Leadership Square
211 N. Robinson, Tenth Floor
Oklahoma City, OK 73102 (US)

Low NO_x axial premix burner apparatus and methods for burning fuel gas are provided by the present invention. The methods of the invention are basically comprised of the steps of mixing a first portion of the fuel gas and all of the air to form a lean primary fuel gas-air mixture, discharging the lean primary fuel gas-air mixture into the furnace space whereby the mixture is burned in a primary combustion zone therein, discharging a second portion of the fuel gas into the primary combustion zone to stabilize the flame produced therein and discharging the remaining portion of the fuel gas into a secondary combustion zone in the furnace space.

(21) **Appl. No.:** **09/726,937**(22) **Filed:** **Nov. 30, 2000**






FIG. 3




FIG. 4

LOW NO_x PREMIX BURNER APPARATUS AND METHODS

BACKGROUND OF THE INVENTION

[0001] 1. Field of the Invention

[0002] The present invention relates to low NO_x producing burner apparatus and methods, and more particularly, to low NO_x axial premix burner apparatus and methods.

[0003] 2. Description of the Prior Art

[0004] Because of stringent environmental emission standards adopted by government authorities and agencies, burner apparatus and methods have heretofore been developed which suppress the formation of nitrogen oxides (NO_x) in flue gases produced by the combustion of fuel-air mixtures. For example, burner apparatus and methods wherein liquid or gaseous fuel is burned in less than a stoichiometric concentration of air to lower the flame temperature and thereby reduce thermal NO_x have been developed. That is, staged air burner apparatus and methods have been developed wherein the fuel is burned in a deficiency of air in a first combustion zone whereby a reducing environment which suppresses NO_x formation is produced, and the remaining portion of the air is introduced into a second zone downstream from the first zone wherein the unburned remaining fuel is combusted.

[0005] Staged fuel burner apparatus have also been developed wherein all of the air and some of the fuel is burned in a first zone with the remaining fuel being burned in a second downstream zone. In such staged fuel burner apparatus and methods, an excess of air in the first zone functions as a diluent which lowers the temperature of the burning gases and thereby reduces the formation of NO_x.

[0006] While staged fuel burners which produce flue gases containing low levels of NO_x have been utilized heretofore, there are continuing needs for improved axial premix burner apparatus having high firing capacities and producing flue gases having ultra low NO_x emission levels and methods of using the apparatus.

SUMMARY OF THE INVENTION

[0007] By the present invention low NO_x axial premix burner apparatus and methods are provided which meet the needs described above and overcome the deficiencies of the prior art. That is, in accordance with the present invention, a low NO_x forming premix burner apparatus for burning gaseous fuels adapted to be connected to a furnace space is provided. The burner apparatus includes a housing having a discharge end attached to the furnace space and a closed opposite end. Means for introducing air into the housing are attached thereto and a burner tile having an opening there-through and optionally including a flame stabilizing block as a part thereof is disposed within the furnace space adjacent to the burner housing. At least one elongated primary fuel gas and air venturi mixer is disposed within the housing having an open inlet end positioned adjacent to the closed end of the housing and a primary fuel gas-air mixture discharge nozzle attached to the other end thereof. The discharge nozzle extends into the burner tile through the opening therein and is positioned so that the flame produced by the burning of the primary fuel gas-air mixture is projected in a direction which is axial to the burner housing and

impinges on the flame stabilizing block when it is utilized. A first primary fuel gas nozzle connected to a source of pressurized fuel gas is positioned to discharge a primary gas fuel jet into the open inlet end of the elongated venturi mixer whereby air from within the housing is drawn into the mixer, the air is mixed with the primary fuel gas therein and the resulting primary fuel gas-air mixture is discharged by the discharge nozzle and burned in the burner tile and in the furnace space. A second primary fuel gas nozzle connected to a source of pressurized fuel gas is positioned within the burner tile to discharge additional primary fuel gas into the flame therein whereby the flame is further stabilized. At least one secondary fuel gas nozzle connected to a source of pressurized fuel and positioned to discharge secondary fuel gas within the furnace space is provided whereby the secondary fuel gas mixes with air and flue gases in the furnace space and is burned therein.

[0008] The methods of the present invention basically comprise the following steps. (a) mixing a first portion of the fuel gas and all of the air to form a lean primary fuel gas-air mixture; (b) discharging the lean primary fuel gas-air mixture into a furnace space whereby the mixture is burned in a primary combustion zone therein and flue gases having very low NO_x content are formed therefrom; (c) discharging a second portion of the fuel gas into the primary combustion zone whereby the second portion of the fuel gas is mixed with air and is burned to further stabilize the flame produced therein; and (d) discharging the remaining portion of the fuel gas into a secondary combustion zone in the furnace space wherein the remaining portion of the fuel gas mixes with air in the furnace space and with flue gases therein to form a second fuel gas-air mixture diluted with flue gases whereby the mixture is burned in the secondary combustion zone and additional flue gases having very low NO_x content are formed therefrom. The flame produced in the primary combustion zone by the burning of the lean primary fuel gas-air mixture discharged in accordance with step (a) can optionally contact a flame stabilizing block in the furnace space.

[0009] It is, therefore, a general object of the present invention to provide an improved low NO_x axial premix burner apparatus and methods of burning an at least substantially stoichiometric mixture of fuel gas and air whereby flue gases having very low NO_x content are formed therefrom.

[0010] Other and further objects, features and advantages of the present invention will be readily apparent to those skilled in the art upon a reading of the description of preferred embodiments which follows when taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0011] FIG. 1 is a side elevational view of the burner apparatus of the present invention attached to a furnace space.

[0012] FIG. 2 is an end view of the burner apparatus taken along line 2-2 of FIG. 1.

[0013] FIG. 3 is an opposite end view of the burner apparatus taken along line 3-3 of FIG. 1.

[0014] FIG. 4 is a cross-sectional view of the burner apparatus taken along line 4-4 of FIG. 3.

DESCRIPTION OF PREFERRED EMBODIMENTS

[0015] The present invention provides a low NO_x axial premix burner which provides a high heat release and a high burner efficiency while maintaining very low NO_x formation. The burner apparatus can achieve very high firing capacity, a variety of flame shapes, excellent stability and very low NO_x emissions which meet desired performance specifications. The burner apparatus may be utilized to fire horizontally along a furnace floor, vertically up a furnace wall or at an angle along a furnace wall. Other advantages of the burner apparatus and methods of this invention will be apparent to those skilled in the art from the following description.

[0016] Referring now to the drawings, the low NO_x premix axial burner apparatus of the present invention is illustrated and generally designated by the numeral 10. The burner 10 includes a housing 12 having an open discharge end 14 and a closed opposite end 16. As illustrated in FIG. 1, the open end 14 of the housing 12 is adapted to be connected to an opening 18 in a wall 20 of a furnace. As will be understood by those skilled in the art, the furnace wall 18 generally includes an internal layer of insulation material 22 and the wall 20 and insulation material 22 define a furnace space 24 within which fuel and air are burned to form hot flue gases.

[0017] As shown in FIG. 2, an air register 26 is sealingly connected over an opening (not shown) in a side of the housing 12 for introducing a controlled quantity of air into the housing 12. The air register 26 includes louvers 28 or the like which can be adjusted by means of a handle 29 to control the quantity of air flowing therethrough and into the housing 12.

[0018] A burner tile generally designated by the numeral 28 is attached to the open inlet end 14 of the housing 12 and extends into the furnace space 24 as shown in FIGS. 1 and 4. In an alternate arrangement, the burner tile 28 can be disposed in the furnace space 24 sealingly attached over the opening 18 in the wall 20 of the furnace space 24. The burner tile 28 is formed of a heat and flame resistant ceramic material and can be molded as a single part or it can be formed of a plurality of parts as shown in FIGS. 1 and 3. The burner tile 28 includes two openings 30 (FIG. 3) for receiving discharge nozzles 32 connected to a pair of fuel gas and air venturi mixers which will be described further hereinbelow. The openings 30 and the discharge nozzles 32 are surrounded by the side and bottom walls 34, 36, 38 and 40 of the burner tile 28. The center portion of the burner tile 28 surrounding the discharge nozzles 32 includes an opening 42 therein. Also, a flame stabilizing block 44 can optionally be attached to or otherwise positioned adjacent to the bottom wall 38 of the burner tile 28.

[0019] As shown in FIGS. 1, 3 and 4, a pair of fuel gas and air venturi mixers 46 are axially disposed within the housing 12. The elongated venturi mixers 46 each include an open end 48 positioned adjacent to the closed end 16 of the housing 12 with the other end being connected to a previously mentioned discharge nozzle 32. The discharge nozzles 32 are positioned at slight angles such that the fuel gas and air mixtures discharged through the nozzles 32 and the flame produced from their combustion is projected towards the flame stabilizing block 44 when it is utilized. Each of the

venturi mixers 46 includes an adjustable air door assembly at the open inlet end thereof generally designated by the numeral 50 (FIG. 1). Control handles 52 which are a part of the assemblies 50 are utilized to control and balance the air entering the venturi mixers 46.

[0020] As best shown in FIGS. 1 and 4, a closed compartment generally designated by the numeral 54 is disposed within the housing 20 and sealingly attached over the opening 18 in the furnace space 24. The closed compartment 54 includes an opening 56 therein (FIG. 4) and a door 58 is hinged to the compartment 54 over the opening 56. The door 58 is connected to a rod 60 which is in turn connected to a control handle mounted on the outside of the closed end of the housing 12 for opening and closing the door 58. When the door 58 is opened, air from within the housing 12 flows through the opening 56 into the closed compartment 54 and then flows into the furnace space 24 by way of the opening 42 in the burner tile 28. While the door 58 can be used to allow a controlled rate of secondary air into the furnace space 24, it is normally only used when the fuel gas-air mixtures discharged from the venturi mixers 46 are initially ignited as will be described hereinbelow.

[0021] A pair of primary fuel gas nozzles 64 are attached to the closed end 16 of the housing 12 and are positioned to discharge primary fuel gas jets into the open ends 48 of the venturi mixers 46 (only one of the nozzles 64 and one venturi mixer 46 are shown in FIG. 1). Each of the primary fuel gas nozzles 64 is connected by a conduit 66 to a fuel gas header 68 as shown in FIGS. 1 and 2. As will be understood by those skilled in the art, the primary fuel gas jets discharged into the open ends 48 of the venturi mixers 46 cause air from within the housing 12 to be drawn into the venturi mixers 46 whereby the air mixes with the discharged primary fuel gas and the resulting mixtures exit the venturi mixers 46 by way of the discharge nozzles 32 attached thereto. The discharge nozzles 32 include a plurality of openings therein designed to provide the total exit area necessary for the fuel gas-air mixtures from the venturi mixers to flow through the discharge nozzles. Also, as is well understood by those skilled in the art, the discharge nozzles 32 are of a design to insure that the burner 10 can be operated without the occurrence of flash backs.

[0022] A pair of secondary fuel gas nozzles (staged fuel gas nozzles) 70 are positioned at the end of the burner tile 28 within the furnace space 24. The secondary fuel gas tips 70 are positioned above and on opposite sides of the two fuel gas-air mixture discharge nozzles 32, and the nozzles 70 are oriented so that the secondary fuel gas is discharged into a secondary combustion zone downstream of the primary combustion zone within the furnace space 24.

[0023] The flame produced by the burning of the primary fuel gas-air mixtures discharged from the nozzles 32 impinges on the flame stabilizing block 44 when it is utilized causing the block to be heated, stabilizing the flame and establishing a mixing zone within the primary combustion zone in the furnace space 24. Because the primary fuel gas-air mixtures discharged into the primary combustion zone contain excess air, the flue gases generated in the primary combustion zone have a very low NO_x content. The secondary fuel gas discharged by the secondary fuel gas nozzles 70 into the secondary combustion zone mixes with air remaining in the furnace space and with flue gases

contained therein to form a second fuel gas-air mixture diluted with flue gases which is burned in the secondary combustion zone forming additional flue gases having very low NO_x content. The secondary fuel gas nozzles 70 are connected by conduits 72 within the housing 12 and by conduits 74 outside the closed end 16 of the housing 12 to the fuel gas inlet header 68.

[0024] In order to further stabilize the flame produced in the primary combustion zone in addition to the flame stabilization brought about by the stabilizing block 44 when it is used, a primary fuel gas nozzle 76 is positioned adjacent to the primary fuel gas-air discharge nozzles 32. That is, the primary fuel gas nozzle 76 is positioned below and between the discharge nozzles 32 as best shown in FIG. 3. The primary fuel gas nozzle 76 is connected by a conduit 78 within the housing 12 and a conduit 80 outside the housing 12 to the fuel gas inlet header 68. The primary fuel gas discharged into the primary combustion zone by the fuel gas nozzle 76 mixes with air in the primary combustion zone and forms a fuel gas-air mixture therein which is substantially stoichiometric. The burning of that mixture in the primary combustion zone functions to stabilize the overall flame produced.

[0025] A conduit 82 for facilitating the ignition of the primary fuel gas-air mixtures discharged by the venturi mixer discharge nozzles 32 is sealingly connected through the closed end 16 of the housing 12 and through and into the closed compartment 54. A cover door is attached to the housing 12 over the outside end of the conduit 82. As will be understood by those skilled in the art, a torch is inserted through the conduit 82 into the closed compartment 54 and through the opening 42 for igniting the primary fuel gas-air mixture exiting the nozzles 32. Prior to inserting the torch, the air door 58 in the closed compartment 54 is opened to insure that fuel gas does not enter the closed compartment 54 prior to ignition.

[0026] As will be understood by those skilled in the art, depending on the design conditions to be met by the burner apparatus 10, the burner apparatus can include one or more primary fuel gas-air venturi mixers, one or more first primary fuel gas nozzles for injecting primary fuel gas into the venturi mixer or mixers, one or more second primary fuel gas nozzles for stabilizing the flame in the primary combustion zone and one or more secondary fuel gas nozzles for introducing fuel gas into the secondary combustion zone. Further, a single primary fuel gas-air venturi mixer having a plurality of primary fuel nozzles therein for causing air to be drawn into the venturi mixer can be used.

[0027] The methods carried out by the burner apparatus of this invention, i.e., the methods of discharging an at least substantially stoichiometric mixture of fuel gas and air into a furnace space wherein the mixture is burned and flue gases having very low NO_x content are formed therefrom, are basically comprised of the following steps: (a) a first portion of the fuel gas (referred to herein as primary fuel gas) and all of the air are mixed in the venturi mixers 46 to form lean primary fuel gas-air mixtures; (b) the lean primary fuel gas-air mixtures are discharged into the furnace space 24 whereby the mixtures are burned in a primary combustion zone therein, the flame produced optionally contacts a flame stabilizing block 44 in the furnace space 24 and is stabilized thereby and flue gases having very low NO_x content are

formed therefrom; (c) a second portion of the fuel gas (also referred to as primary fuel gas) is discharged into the primary combustion zone whereby the second portion of the primary fuel gas is mixed with air and is burned to stabilize the flame produced in the primary combustion zone; and (d) the remaining portion of the fuel gas (referred to as secondary fuel gas) is discharged into a secondary combustion zone in the furnace space 24 wherein the remaining portion of the fuel gas mixes with air remaining in the furnace space 24 and with flue gases contained therein to form a second fuel gas-air mixture diluted with flue gases whereby the mixture is burned in the secondary combustion zone and additional flue gases having very low NO_x content are formed therefrom.

[0028] As mentioned above, depending upon the particular application involved, the above described method can be carried out in a burner apparatus of this invention having one or more primary fuel gas-air venturi mixers, one or more first primary fuel gas nozzles for injecting primary fuel gas into the venturi mixer or mixers, one or more second primary fuel gas nozzles for stabilizing the flame in the primary combustion zone and one or more secondary fuel gas nozzles for introducing fuel gas into the secondary combustion zone.

[0029] The lean mixture of the first portion of the primary fuel gas and air which is discharged into the primary combustion zone is generally a mixture having a stoichiometric ratio of fuel gas to air of about 1.5:4. The first portion of the primary fuel gas in the lean primary fuel gas-air mixture is also generally an amount in the range of from about 30% to about 70% by volume of the total fuel gas discharged into the furnace space. The second portion of the primary fuel gas discharged into the primary combustion zone to stabilize the flame is generally an amount in the range of from about 2% to about 25% by volume of the total fuel gas discharged into the furnace space. The remaining portion of the fuel gas, i.e., the secondary fuel gas, is generally discharged into the secondary combustion zone in an amount in the range of from about 25% to about 68% by volume of the total fuel gas discharged into the furnace space.

[0030] In order to further illustrate the burner apparatus and methods of the present invention, the following example is given.

EXAMPLE

[0031] A burner apparatus 10 designed for a heat release of 4.8 BTU per hour by burning fuel gas having a caloric value of 1160 BTU per SCF is fired into the furnace space 24. Pressurized fuel gas is supplied to the burner 10 at a pressure of about 45 psig and at a rate of 4100 SCF per hour. A portion of the fuel gas flows into and through the primary fuel gas and air venturi mixers 46 wherein the fuel gas is mixed with air. The lean primary fuel gas-air mixtures formed in the venturi mixers 46 are discharged into a primary combustion zone in the furnace space wherein they are burned and the flame produced contacts the flame stabilizing block 44 and is stabilized thereby. A second portion of the fuel gas is discharged into the furnace space 24 by way of the primary fuel gas nozzle 76 wherein it is mixed with air and is burned to further stabilize the flame produced in the primary combustion zone. The remaining

portion of the fuel gas is discharged into the furnace space by way of the secondary fuel gas nozzles 70. In this example, the rate of air introduced in the housing 12 is controlled by means of the damper 28 such that the total rate of air introduced into the furnace space 24 is an amount which results in 15% excess air therein. All of the air is introduced into the furnace space 24 by way of the venturi mixers 46.

[0032] The secondary fuel gas discharged from the secondary fuel nozzles 70 mixes with the air remaining in the furnace space 24 and relatively cool flue gases therein to form a flue gases diluted fuel-air mixture which is burned in a secondary combustion zone adjacent to the primary combustion zone in the furnace space 24.

[0033] As a result of the burning of the lean primary fuel gas-air mixture in the primary combustion zone and the flue gases diluted secondary fuel gas-air mixture in the secondary combustion zone, the flue gases exiting the furnace space 24 have a very low NO_x content. That is, the flue gases withdrawn from the furnace space 24 have a NO_x content of less than about 12 ppm.

[0034] Thus, the present invention is well adapted to carry out the objects and the ends and advantages mentioned as well as those which are inherent therein. While presently preferred embodiments of the invention have been described for purposes of this disclosure, numerous changes in the construction and in the arrangement of parts and steps will suggest themselves to those skilled in the art which are encompassed within the spirit of this invention as defined by the appended claims.

What is claimed is:

1. A low NO_x axial premix burner apparatus for burning fuel gas adapted to be attached to an opening in a furnace space comprising:

a housing having a discharge end attached to said opening in said furnace space and a closed opposite end;

means for introducing air into said housing attached thereto;

a burner tile having an opening therethrough attached to said discharge end of said housing or otherwise disposed within said furnace space adjacent to said opening therein;

at least one elongated primary fuel gas and air venturi mixer disposed within said housing having an open inlet end positioned adjacent to said closed end of said housing and a primary fuel gas-air mixture discharge nozzle attached to the other end thereof;

a first primary fuel gas nozzle connected to a source of pressurized fuel gas positioned to discharge a primary fuel gas jet into said open inlet end of said elongated venturi mixer whereby air from within said housing is drawn into said mixer, mixed with said primary fuel-gas therein and the resulting primary fuel gas-air mixture is discharged by said discharge nozzle and burned in said burner tile and in said furnace space;

a second primary fuel gas nozzle connected to a source of pressurized fuel gas and positioned within said burner tile for discharging additional primary fuel gas into said flame therein to stabilize said flame; and

at least one secondary fuel gas nozzle connected to a source of pressurized fuel gas and positioned to discharge secondary fuel gas within said furnace space whereby said secondary fuel gas mixes with air and flue gases in said furnace space and is burned therein.

2. The burner apparatus of claim 1 which further comprises a flame stabilizing block attached to said burner tile or otherwise positioned in said furnace space so that the flame produced by the burning of said primary fuel gas-air mixture discharged by said discharge nozzle impinges on said flame stabilizing block and is stabilized thereby.

3. The burner apparatus of claim 1 which further comprises an air passage in said burner tile and a closed compartment disposed within said housing and sealingly attached over said opening in said furnace space, said compartment having an air door therein which can be selectively opened to allow air to flow into said compartment and through said air passage in said burner tile into said furnace space.

4. The burner apparatus of claim 1 which further comprises one or more additional elongated primary fuel gas and air venturi mixers having discharge nozzles attached thereto and extending into said burner tile through openings therein and having first primary fuel gas nozzles positioned to discharge primary fuel gas jets into said open inlet ends thereof.

5. The burner apparatus of claim 1 which further comprises one or more additional second primary fuel gas nozzles positioned within said burner tile to further stabilize said flame.

6. The burner apparatus of claim 1 which further comprises one or more additional secondary fuel gas nozzles.

7. The burner apparatus of claim 3 which further comprises a conduit for facilitating the ignition of said primary fuel gas-air mixture discharged by said venturi mixer discharge nozzle sealingly connected through said closed end of said housing at one end and sealingly connected through and into said closed compartment disposed within said housing at the other end.

8. A low NO_x premix axial burner apparatus for burning fuel gas adapted to be attached to an opening in a furnace space comprising:

a housing having a discharge end attached to said opening in said furnace space and a closed opposite end;

means for introducing air into said housing attached thereto;

a burner tile having a pair of openings therethrough attached to said discharge end of said housing or otherwise disposed within said furnace space adjacent to said opening therein, said burner tile including a flame stabilizing block as a part thereof;

a pair of elongated primary fuel gas and air venturi mixers disposed within said housing, each having an open inlet end positioned adjacent to said closed end of said housing and a primary fuel gas-air mixture discharge nozzle attached to the other end thereof, said discharge nozzles extending into said burner tile through said openings therein and being positioned therein so that the flame produced by the burning of said primary fuel gas-air mixtures discharged by said discharge nozzles impinges on said flame stabilizing block and is stabilized thereby;

a pair of first primary fuel gas nozzles connected to a source of pressurized fuel gas, each positioned to discharge a primary fuel gas jet into an open inlet end of one of said elongated venturi mixers whereby air from within said housing is drawn into said mixers, mixed with said primary fuel-gas therein and the resulting primary fuel gas-air mixtures are discharged by said discharge nozzles and burned in said burner tile and in said furnace space;

a second primary fuel gas nozzle connected to a source of pressurized fuel gas and positioned within said burner tile to discharge additional primary fuel gas into said flame therein to further stabilize said flame; and

a pair of secondary fuel gas nozzles connected to a source of pressurized fuel and positioned to discharge secondary fuel gas within said furnace space whereby said secondary fuel gas mixes with air and flue gases in said furnace space and is burned therein.

9. The burner apparatus of claim 8 which further comprises an air passage in said burner tile and a closed compartment disposed within said housing and sealingly attached over said opening in said furnace space, said compartment having an air door therein which can be selectively opened to allow air to flow into said compartment and through said air passage in said burner tile into said furnace space.

10. The burner apparatus of claim 9 which further comprises a conduit for facilitating the ignition of said primary fuel gas-air mixtures discharged by said venturi mixer discharge nozzles sealingly connected through said closed end of said housing at one end and sealingly connected through and into said closed compartment disposed within said housing at the other end.

11. The burner apparatus of claim 10 wherein said air passage in said burner tile is positioned between said venturi mixer discharge nozzle openings in said burner tile.

12. A method of discharging an at least substantially stoichiometric mixture of fuel gas and air into a furnace space wherein said mixture is burned and flue gases having low NO_x content are formed therefrom comprising the steps of:

- (a) mixing a first portion of said fuel gas and all of said air to form a lean primary fuel gas-air mixture;
- (b) discharging said lean primary fuel gas-air mixture into said furnace space whereby said mixture is burned in a primary combustion zone therein and flue gases having low NO_x content are formed therefrom;
- (c) discharging a second portion of said fuel gas into said primary combustion zone whereby said second portion

of said fuel gas is mixed with air and is burned to stabilize said flame produced therein; and

- (d) discharging the remaining portion of said fuel gas into a secondary combustion zone in said furnace space wherein said remaining portion of said fuel gas mixes with air remaining in said furnace space and with flue gases contained therein to form a second fuel gas-air mixture diluted with flue gases whereby said mixture is burned in said secondary combustion zone and additional flue gases having low NO_x content are formed therefrom.

13. The method of claim 12 which further comprises the step of providing a flame stabilizing block in said furnace space positioned so that the flame produced by the burning of said lean primary fuel gas-air mixture therein impinges on said flame stabilizing block and is stabilized thereby.

14. The method of claim 12 wherein said lean primary fuel gas-air mixture is formed in a primary fuel gas and air venturi mixer and discharged into said primary combustion zone through a discharge nozzle attached thereto.

15. The method of claim 12 wherein said lean primary fuel gas-air mixture is formed in two or more primary fuel gas and air venturi mixers and discharged into said primary combustion zone through discharge nozzles attached thereto.

16. The method of claim 12 wherein said remaining portion of said fuel gas is discharged into said secondary combustion zone by at least one secondary fuel gas nozzle.

17. The method of claim 12 wherein said lean primary fuel gas-air mixture discharged into said furnace space has a stoichiometric ratio of fuel gas to air of about 1.5:4.

18. The method of claim 12 wherein said first portion of said fuel gas in said lean primary fuel gas-air mixture discharged into said furnace space is an amount in the range of from about 30% to about 70% by volume of the total fuel gas discharged into said furnace space.

19. The method of claim 12 wherein said second portion of said fuel gas discharged into said furnace space is an amount in the range of from about 2% to about 25% by volume of the total fuel gas discharged into said furnace space.

20. The method of claim 12 wherein said remaining portion of said fuel gas discharged into said furnace space is an amount in the range of from about 25% to about 68% by volume of the total fuel gas discharged into said furnace space.

* * * * *